

Andersons Golf Products

27-3-11

with Fe, Mn

Turf Fertilizer

- Combines two patented technologies, Extend™ and NS-54 nitrogen.
- Provides an excellent nitrogen feeding program with two slow release nitrogen sources

Guaranteed Analysis

Total Nitrogen (N)	27.00%
0.64% Ammoniacal Nitrogen	
26.36% Urea Nitrogen*	
Available Phosphate (P ₂ O ₅)	3.00%
Soluble Potash (K ₂ O)	11.00%
Sulfur (S)	1.20%
1.20% Free Sulfur (S)	
Iron (Fe)	1.00%
Manganese (Mn)	2.00%
0.29% Water Soluble Manganese (Mn)	

Derived from ammonium phosphate, polymer coated urea, polymer coated sulfur coated urea, potassium chloride, iron sulfate and manganese sulfate.

Chlorine (Cl) Max 9.30%

* 26.36% slowly available urea nitrogen from polymer coated urea and polymer coated sulfur coated urea.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.html>

DIRECTIONS FOR USE

Apply only as directed. Use Andersons Golf Products 27-3-11 with Fe, Mn whenever a high potassium and controlled-release nitrogen fertilization is desired along with iron and manganese.

Phosphate Notice: This lawn/turf fertilizer contains phosphorus and is only for nonagricultural use on (i) turf during its first growing season, (ii) on turf areas being repaired or renovated, and (iii) on turf where a soil test performed within the last 3 years indicates a phosphorus deficiency. This fertilizer is not for the routine maintenance of turf.

Application Rates:

- LOW: 3.70 lbs/1,000 sq. ft.
- MEDIUM: 4.63 lbs/1,000 sq. ft.
- HIGH: 5.56 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS:

We recommend that you follow the Florida Green Industries BMP's at: <http://www.flrules.org/Gateway/reference.asp?No=Ref-04706>

We recommend that you follow the Florida Golf Course BMP's at: <http://www.flrules.org/Gateway/reference.asp?No=Ref-04702>

For all applications:

- For use on fairways and roughs.
- DO NOT USE ON GREENS.
- Do not apply with a drop-type spreader.
- Do not apply at rates lower than recommended to prevent mottling.
- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles in the turf canopy and to avoid possible staining.
- Do not collect clippings for at least one mowing following application to prevent particle pick-up.

Cool Season Grasses

- Apply at LOW or MEDIUM RATE.
- Apply at HIGH RATE in spring or fall for deeper greening or when a higher potassium fertilization is desired.
- **Exception:** Apply at LOW RATE in mid-summer when temperatures are above 80°F.

Warm Season Grasses

- Apply at LOW or MEDIUM RATE.
- HIGH RATE may be used in early spring to help bring grasses out of dormancy (such as bermudagrass) or when a higher potassium fertilization is desired.
- **Exception:** Apply at LOW RATE during mid-summer when temperatures are extreme (90°F or above).

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

Notice: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. **DO NOT WASH OFF WITH WATER.**

STORAGE AND USE

Store in a clean, dry place
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of USA



Manufactured by:
The Andersons, Inc.
P. O. Box 119
Maumee, OH 43537
AndersonsPro.com

The Andersons logo is a registered trademark of The Andersons, Inc. Extend is a trademark of The Andersons, Inc.

Not to be sold through eCommerce without prior written consent of The Andersons.

Follow us on social!

 @TheAndersonsPro
 AndersonsPro

Suggested Spreader Settings					
Suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product.					
50 lbs. covers 13,500 sq. ft. (0.31 acre) with 1.0 lbs. N/1,000 sq. ft. at the LOW RATE (3.70 lbs/1,000 sq. ft.)					
50 lbs. covers 10,700 sq. ft. (0.25 acre) with 1.25 lbs. N/1,000 sq. ft. at the MEDIUM RATE (4.63 lbs/1,000 sq. ft.)					
50 lbs. covers 8,900 sq. ft. (0.20 acre) with 1.50 lbs. N/1,000 sq. ft. at the HIGH RATE (5.56 lbs/1,000 sq. ft.)					
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LOW RATE 3.70 lbs/1,000 sq. ft.	MEDIUM RATE 4.63 lbs/1,000 sq. ft.	HIGH RATE 5.56 lbs/1,000 sq. ft.
Andersons 2000 series (cone 3); Andersons LCO-1000	3 mph	10 feet	L 3/4	M 3/4	O 1/4
Scotts R-8, R-8A (cone 3)	3 mph	10 feet	K 3/4	L 1/2	N
Lesco 020093 (pattern 0.25)	3 mph	8 feet	F	F 1/2	G
Lesco 705698 (pattern 0.25)	3 mph	8 feet	14	15	16
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-C	4.5 mph	38 feet	6	6 1/2	7 1/4
Vicon 03 Series	4.5 mph	30 feet	30	35	38

SGN 240
Net Wt. 50 Lbs. (22.68 kg)



10004888